

## APT02 Control Center set

The Easywave Control Center set (CCset) includes the server (CCserv) and the RX09 USB stick.

With the Easywave CCset and the Easywave Control Center App (CCapp) for

- iOS version 8 and above,
- Android version 4.4 and above,

Easywave products can be comfortably and conveniently controlled and visualized using a smartphone or tablet.

This can be done locally in the server WLAN network or, if the server is linked up to a home network, in the home network itself. If the chargeable remote function is enabled, control and visualization is also possible via a remote network connection.



APT02CCset-01-02K

### Technical specifications APT02 CCserv

|                   |   |
|-------------------|---|
| Power consumption | 5.0 W on average  |
| Interfaces        | <ul style="list-style-type: none"> <li>• WLAN 802.11 b/g/n</li> <li>• LAN connection (up to 1000 MBit/s)</li> <li>• 2x USB 2.0 ports</li> </ul> |
| Power supply      | 100-240 V AC, 50-60 Hz, maximum 20 W  |
| Dimensions        | 95 x 65 x 48.5 mm   |
| Color             | white similar to RAL 9003   |



### Technical specifications RX09

|               |   |
|---------------|---|
| Coding        | factory coding with 64 Easywave telegrams     |
| Radio inputs  | unlimited                                     |
| Radio outputs | 64  |
| Frequency     | 868.30 MHz                                    |
| Range         | typically 150 m in good free-field conditions |
| Power supply  | via USB port                                  |
| Dimensions    | 24 x 75 x 8 mm                                |
| Color         | white similar to RAL 9003                     |



### Scope of delivery

- APT02 CCserv
- RX09 USB stick
- Ethernet cable (CAT 5)
- Plug for 230V Schuko socket

### Models

| Product numbers   | Description  |
|-------------------|--|
| APT02CCset-01-02K | Control Center set includes the APT02 CCserv server and the RX09 Radio USB stick |