

RTS22 Wall switch CALL

Format 55



The RTS22 wall switch CALL from the Format 55 series is a battery-operated Easywave transmitter with a call-button.

This complete version of the RTS22 wall switch contains all the components required to be put into operation immediately. The transmitter module, a white frame and a white single rocker are included in the scope of delivery.

If necessary, the wall switch can be used in cover frames from other manufacturers (see compatibility list).

It can be used for paging in conjunction with the RCP25 socket pager, the RCP24 radio bell or the Easywave Fon Alarm. A connection to care systems, e.g. as a call button for nurse call systems, is also possible.



RTS22E5001A05

Technical specifications

Coding	Easywave
Frequency	868.30 MHz
Channels	1
Range	typically 150 m in good free-field conditions
Power supply	1x 3V-battery, CR2032
Operation	transmission lasts as long as the button is pressed (maximum 36 seconds)
Operating temperature	-20°C to +60°C
Dimensions (W/L/H)	
Mounting plate	71/71/1.8 mm
Rocker	55/55/9.0 mm
Cover frame	80/80/9.4 mm
Weight	44 g (including battery and cover frame)
Color	white similar RAL 9003

Accessories (optional)



Single rocker CALL
white RTS22-ACC-07

Scope of delivery

- Transmitter module incl. battery
- Rocker CALL, white
- Cover frame
- Mounting plate
- Adhesive pad
- Operating manual

Accessories (optional)

RTS22-ACC-01-01P	Mounting plate, white
RTS22-ACC-05	Cover frame, white



RTS22-ACC-01-01P



RTS22-ACC-05

Models

Product number	Description
RTS22E5001A05	Wall switch single rocker CALL complete, Easywave, 1x PULSE, Format 55, white